
Aussie Pumps

AUSSIE PUMP SELECTION GUIDE



NO electric power available on site

- 1. Select type of engine permitted/requested
- 2. Select type of liquid to be pumped
- 3. Match flow & head requirement



Petrol or Diesel?

Petrol

Type of liquid to be transferred

Clean water transfer

Solids contaminated water Diesel fuel Transfer

Aussie QP Transfer, high pressure & fire pumps

1-6" ... heads to 95m flows to 2900 lpm Self priming



Pump Smart ... p3-11

Aussie QP Trash pumps

2-4" ... heads to 27m flows to 1800 lpm Solids to 1.5"



Pump Smart ...

Aussie Fuel Master

2-3" ... heads to 75m flows to 1000lpm Viton seals fitted



Pump Smart ... p21

Diesel

Type of liquid to be transferred

Clean water transfer

Solids contaminated water

Diesel fuel Transfer

Aussie QP Transfer & high pressure pumps

2-6" ... heads to 90m flows to 2500 lpm Self priming



Pump Smart ... p9, 12-13

Aussie QP Trash pumps

2-6" ... heads to 46m flows to 6,000lpm Solids to 3"



Pump Smart ... p15-19 Aussie Fuel Master

2-3" ... heads to 60m flows to 1000lpm Viton seals fitted




Pump Smart ... p21




Aussie Pumps

AUSSIE PUMP SELECTION GUIDE



Electric power available on site

- 1. Select type of power available
- 2. Select type of liquid to be transferred
- 3. Match flow & head requirement



240v or 415v?

240v

Type of liquid to be transferred

Spill (water) clean-up

Puddle Sucker

Tsurumi

1" ...

LSC series

heads to 11m

Solids to 6mm

Pumps down to

Tsurumi catalogue

flows to 170 lpm

General dewatering

Tsurumi

HS / HSZ

(Manual/Auto)

Solids contaminated water

High head dewatering

Tsurumi **HSD**

2" ... 2" ... heads to 18m flows to 300 lpm Solids to 7mm



Tsurumi catalogue

heads to 13m flows to 220 lpm Solids to 10mm Agitator fitted ..



Tsurumi catalogue

Tsurumi NK

3" ... heads to 24m flows to 525 lpm Solids to 6mm



Tsurumi catalogue

415_v

Type of liquid to be transferred

General dewatering **Solids** contaminated water

Tsurumi KTZ / KTZE (Manual/Auto)

2 - 4" ... heads to 48m flows to 2,440 lpm Solids to 10mm



Tsurumi catalogue

Tsurumi KTD

2 -3" ... heads to 22m flows to 800 lpm Solids to 10mm Agitator fitted .. stirs silt



Tsurumi catalogue

For effluent, sewage & chemical handling submersibles ... see Tsurumi 2017 catalogue

